



INNERSPACE

CHESHIRE

OAK

QUERCUS

O & M

SPECIFICATION

Introduction

Innerspace Cheshire QUERCUS Squared panels are suitable for internal use.
No maintenance is required other than light dusting once in a while use.

Specification

Standard Composition	6mm Zero formaldehyde MDF carrier. 15mm end grain oak, stained / oiled or whitewashed depending on the colour choice Inserts are of real metal laminate, NATUREMOSS Lowland or BARKWALL Poplar – other inserts on request.
Tile size	150mm (w) * 150mm (h)
Tile Thickness	21mm (d)
Weight	Approx 10Kg / Sq. m
Packaging	Recycled cardboard – containing 9 panels (ca 0.2 Sq. m)
Fire	An FR treated version is available on request

INSTALLATION

Installation

Tiles should be installed using adhesive.

MAINTENANCE

Maintenance

Generally, no specific maintenance is required.

Light dusting should be undertaken to remove any debris that has settled.

The moss element can become dry if humidity is very low – restore comfortable humidity levels and it will become moist again.

When dry it is vulnerable to damage so try to avoid this.

If the moss is damaged the panels can be repaired. Contact us to organise this.

The moss will fade gently in direct sunlight.

SUSTAINABILITY

Sustainability

QUERCUS Squared is manufactured from FSC oak timber.

The stains are water based.

The design allows the use of end grain timber that might otherwise have been wasted.

We'd love to hear from you...

01270 625 043

Office@innerspacecheshire.co.uk

www.innerspacecheshire.co.uk